# **Shindaiwa®**

# Operator's Manual EB633RT Power Blower

# WARNING

The engine exhaust from this product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

# **▲** WARNING



Read and understand all provided literature before use. Failure to do so could result in serious injury.

Note: This product complies with CAN ICES-2/NMB-2.

# **TABLE OF CONTENTS**

Introduction	. 3
Servicing Information	
Parts and Serial Number	
Service	
Consumer Product Support	. 4
Product Registration	. 4
Additional Literature	. 4
Safety	. 5
Manual Safety Symbols and Important Information	. 5
International Symbols	6
Personal Condition and Safety Equipment	. 8
Equipment	12
Emission Control (Exhaust & Evaporative)	14
CARB and EPA Emissions Control Information	
Description	15
Contents	16
Assembly	17
Install Blower Pipes	17
Operation	18
Fuel	19
Starting Cold Engine	22
Starting Warm Engine	
Stopping Engine	
Operating Blower	
Maintenance	26
Skill Levels	26
Maintenance Intervals	27
Air Filter	28
Fuel Filter	28
Spark Plug	29
Cooling System	
Exhaust System	
Carburetor Adjustment	
Troubleshooting	
Storage	
Long Term Storage (Over 30 Days)	
Specifications	
Product Registration	38

#### INTRODUCTION

Specifications, descriptions, and illustrative material in this literature are as accurate as possible. Specifications are subject to change without notice. Illustrations might include optional equipment and accessories, and might not include all standard equipment. Your equipment might appear slightly different than pictured equipment.



Read and understand all provided literature. Literature contains specifications and information for safety, operation, maintenance, storage, and assembly specific to this product. Scan QR codes for more information.



For additional literature, including safety manuals where applicable, or questions regarding terms used in this manual, visit:

https://www.echo-usa.com/manuals

OR





https://www.shindaiwa-usa.com/manuals

# SERVICING INFORMATION

# Parts and Serial Number

Genuine Shindaiwa Parts and Assemblies for your Shindaiwa products are available only from an Authorized Shindaiwa Dealer. When you do need to buy parts always have the Model Number and Serial Number of the unit with you. For future reference, write them in the space provided below.



Model No.	Serial No.
WIGGELLING.	Ochai No.

#### Service

Service of this product during the warranty period must be performed by an Authorized Shindaiwa Service Dealer. For the name and address of the Authorized Shindaiwa Service Dealer nearest you, ask your retailer or call: 1-877-986-7783. Dealer information is also available on www.shindaiwa-usa.com. When presenting your unit for Warranty service/repairs, proof of purchase is required.

# **Consumer Product Support**

If you require assistance or have questions concerning the application, operation or maintenance of this product you may call the Shindaiwa Consumer Product Support Department at 1-877-986-7783 from 8:00 am to 5:00 pm (Central Standard Time) Monday through Friday. Before calling, please know the model and serial number of your unit.

# **Product Registration**

To ensure trouble free warranty coverage it is important that you register your Shindaiwa equipment on-line at www.shindaiwa-usa.com or by filling out the product registration sheet included in this manual. Registering your product confirms your warranty coverage and provides a direct link between you and ECHO if we find it necessary to contact you.

#### Additional Literature

In addition to finding information online, information is available from your Authorized Shindaiwa Service Dealer, or by contacting ECHO Incorporated, 400 Oakwood Road, Lake Zurich, IL 60047, 1-800-432-ECHO (3246).

EB633RT SAFETY

#### SAFETY

# Manual Safety Symbols and Important Information

Throughout this manual and on the product itself, you will find safety alerts and helpful, informational messages preceded by symbols or key words. The following is an explanation of those symbols and key words and what they mean to you.

# DANGER

The safety alert symbol accompanied by the word "DANGER" calls attention to an act or condition which WILL lead to serious personal injury or death if not avoided.

# WARNING

The safety alert symbol accompanied by the word "WARNING" calls attention to an act or condition which CAN lead to serious personal injury or death if not avoided.

# CAUTION

The safety alert symbol accompanied by the word "CAUTION" calls attention to an act or condition which might lead to minor or moderate personal injury if not avoided.

The enclosed message provides information necessary for the protection of the unit.

Note: This enclosed message provides tips for use, care and maintenance of the unit.



CIRCLE AND SLASH SYMBOL

This symbol means the specific action shown is prohibited. Ignoring these prohibitions can result in serious or fatal injury.

# **International Symbols**

Symbol	Description	Symbol	Description
	Read and Understand the Operator's Manual	Ι	Carburetor Adjustment - High Speed Mixture
	Wear Eye, Ear and Head Protection	T	Carburetor Adjustment - Idle Speed
	Wear Hand Protection	L	Carburetor Adjustment - Low Speed Mixture
$\triangle$	Safety/Alert	STOP	Stop Switch
atalliunklia.	Hot Surface	+6	Fuel and Oil Mixture
<b>A</b>	Idle Speed	<b>P</b>	Fast Speed
	Finger Severing	•	Purge Bulb
	DO NOT Allow Flames or Sparks Near Fuel	Ignition ON OFF O	Ignition ON / OFF
3	DO NOT Smoke Near Fuel	1	Choke Control "COLD START" Position (Choke Closed)

Symbol	Description	Symbol	Description
	Choke Control "RUN" Position (Choke Open)	TY I	Wear Slip Resistant Footwear
		Beware of Thrown Objects	
.09E 15m (50ft)		Keep Bystanders and Helpers Away 15 m (50 ft.).	

Note: Not all symbols will appear on your unit.



SAFETY EB633RT

# Personal Condition and Safety Equipment

# WARNING

Cancer and Reproductive Harm www.P65Warnings.ca.gov

# **WARNING**



The muffler or catalytic muffler and surrounding cover may become extremely hot. Always keep clear of exhaust and muffler area, otherwise serious personal injury might occur.

# WARNING

Users of this product risk injury to themselves and others if the unit is used improperly and/or safety precautions are not followed. Proper clothing and safety gear must be worn when operating unit.

#### **Physical Condition**

Your judgment and physical dexterity may not be good:

- · If you are tired or sick
- If you are taking medication
- · If you have taken alcohol or drugs

Operate unit only if you are physically and mentally well.

# **Eye Protection**

# WARNING

- Eye protection that meets ANSI Z87.1 or CE requirements must be worn whenever you operate the unit.
- For additional safety, a full-face shield can be worn over safety glasses or goggles to provide protection from sharp branches or flying debris.

EB633RT SAFETY

#### **Hand Protection**

Wear sturdy, no-slip, rubber work gloves to improve your grip on the handles. Gloves also provide protection against cuts and scratches, cold environments, and reduce the transmission of machine vibration to your hands.

#### **Hearing and Ear Protection**

ECHO recommends wearing personal protective equipment whenever unit is used.

#### **Breathing Protection**

Operators who are sensitive to dust or other common airborne allergens may need to wear a dust mask to prevent inhaling these materials while operating unit. Dust masks can provide protection against dust, plant debris, and other plant matter such as pollen. Make sure the mask does not impair your vision, and replace the mask as needed to prevent air restrictions.

#### **Proper Clothing**

Wear snug-fitting, durable clothing:

- Pants should have long legs, shirts should have long sleeves.
- DO NOT WEAR SHORTS.
- DO NOT WEAR TIES, SCARVES, JEWELRY, or clothing with loose or hanging items that could become entangled in moving parts or surrounding growth.
- Keep clothing buttoned or zipped, and keep shirt tails tucked in.
- · Wear sturdy work shoes with nonskid rubber soles.
- DO NOT WEAR OPEN TOED SHOES.
- DO NOT OPERATE UNIT WITH BARE FEET.

Keep long hair away from engine and air intake. Retain hair with cap or net.

Heavy protective clothing can increase operator fatigue, which may lead to heat stroke. Schedule heavy work for early morning or late afternoon hours when temperatures are cooler.

# **WARNING**

The components of this machine generate an electromagnetic field during operation, which can interfere with some pacemakers. To reduce the risk of serious or fatal injury, persons with pacemakers should consult with their physician and the pacemaker manufacturer before operating this machine. In the absence of such information, ECHO does not recommend the use of this machine by anyone who has a pacemaker.

**Extended Operation and Extreme Conditions** 

# **A CAUTION**

Prolonged exposure to cold and/or vibration can result in injury. Read and follow all safety and operation instructions to minimize risk of injury. Failure to follow instructions can result in painful wrist/hand/arm injuries.

It is believed that a condition called Raynaud's Phenomenon, which affects the fingers of certain individuals, may be brought about by exposure to vibration and cold. Exposure to vibration and cold may cause tingling and burning sensations, followed by loss of color and numbness in the fingers. The following precautions are strongly recommended, because the minimum exposure, which might trigger the ailment, is unknown.

- Keep your body warm, especially the head, neck, feet, ankles, hands, and wrists.
- Maintain good blood circulation by performing vigorous arm exercises during frequent work breaks, and also by not smoking.
- Limit the hours of operation. Try to fill each day with jobs where operating the unit or other hand-held power equipment is not required.
- If you experience discomfort, redness, and swelling of the fingers followed by whitening and loss of feeling, consult your physician before further exposing yourself to cold and vibration.


EB633RT SAFETY

#### Repetitive Stress Injuries (RSI)

It is believed that overusing the muscles and tendons of the fingers, hands, arms, and shoulders may cause soreness, swelling, numbness, weakness, and extreme pain in those areas. Certain repetitive hand activities may put you at a high risk for developing a Repetitive Stress Injury (RSI). An extreme RSI condition is Carpal Tunnel Syndrome (CTS), which could occur when your wrist swells and squeezes a vital nerve that runs through the area. Some believe that prolonged exposure to vibration may contribute to CTS. CTS can cause severe pain for months or even years.

To reduce the risk of RSI/CTS, do the following

- Avoid using your wrist in a bent, extended, or twisted position. Instead try to maintain a straight wrist position. Also, when grasping, use your whole hand, not just the thumb and index finger.
- Take periodic breaks to minimize repetition and rest your hands.
- Reduce the speed and force with which you do the repetitive movement.
- Do exercises to strengthen the hand and arm muscles.



 Immediately stop using all power equipment and consult a doctor if you feel tingling, numbness, or pain in the fingers, hands, wrists, or arms. The sooner RSI/CTS is diagnosed, the more likely permanent nerve and muscle damage can be prevented.

# A DANGER

All over head electrical conductors and communications wires can have electricity flow with high voltages. This unit is not insulated against electrical current. Never touch wires directly or indirectly, otherwise serious injury or death can result.

# **A** DANGER

Do not operate this product indoors or in inadequately ventilated areas. Engine exhaust contains poisonous emissions and can cause serious injury or death.

SAFETY EB633RT

#### Read the Manual

 Provide all users of this equipment with literature for instructions on safe operation.

#### Clear the Work Area

- Clear the area of children, bystanders, and pets. At a minimum, keep all children, bystanders, and pets outside a 15 m (50 ft.) radius; outside the 15 m (50 ft.) zone, there is still a risk of injury from thrown objects. Bystanders should be encouraged to wear eye protection. If you are approached, stop the engine.
- Avoid blowing debris towards people, pets, open windows, or vehicles when using unit.
- Review area to be cleared. Look for potential hazards such as stones or metal objects.

#### Keep a Firm Grip

 To prevent from dropping the unit, hold the handle in one hand, with thumb and fingers encircling the handle.

#### Keep a Solid Stance

 Maintain footing and balance at all times. Do not stand on slippery, uneven or unstable surfaces. Do not work in odd positions or on ladders. Do not over reach.

#### **Avoid Hot Surfaces**

 Keep exhaust area clear of flammable debris. Avoid contact during and immediately after operation.





# Equipment

# **WARNING**

Use only approved attachments. Serious injury can result from the use of a non-approved attachment combination. ECHO Incorporated will not be responsible for the failure of cutting devices, attachments or accessories which have not been tested and approved by ECHO. Read and comply with all safety instructions listed in this manual.

 Do not attempt to modify this product. Serious injury can result from the use of any modified product. EB633RT SAFETY

 Check unit for loose/missing nuts, bolts, and screws. Tighten and/or replace as needed.

- Do not use blower if any part is missing or damaged.
- Have repairs done only by an authorized service dealer.

# WARNING

Moving parts can amputate fingers or cause severe injuries. Keep hands, clothing and loose objects away from all openings.

- ALWAYS stop engine, disconnect spark plug, and make sure all moving parts have come to a complete stop before removing obstructions, clearing debris, or servicing unit.
- ◆ DO NOT start or operate unit unless all guards and protective covers are properly assembled to unit.
- NEVER reach into any opening while the engine is running. Moving parts might not be visible through openings.

# WARNING

Periodically check fuel system (fuel lines, vent, grommet, fuel tank, and fuel cap) for leaks especially if the unit is dropped. If damage or leaks are found, do not use unit, otherwise serious personal injury or property damage may occur. Have unit repaired by an authorized servicing dealer before using.

# EMISSION CONTROL (EXHAUST & EVAPORATIVE)

#### **CARB and EPA Emissions Control Information**

The emission control system for the engine is EM (engine modification) and, if the second to last character of the Engine Family on the Emission Control Information label (sample below) is "B", "C", "K", or "T", the emission control system is EM and TWC

(3-way catalyst). The fuel tank/fuel

EMISSION CONTROL INFORMATION ENGINE FAMILY: (2) ENDS. 021460 DISPLACEMENT: 21.2cc EMISSION COMPLIANCE PERIOD: SORDOURS HINS ENGINE MEETS 2013 U.S. EPA EXAVEYP & CALIFORNIA EMAKEY BAISSION REQULATIONS FOR S.O.R.E. REFER TO OMNER'S MANUAL FOR MAINTEMANCE SPECIFICATIONS AND ADJUSTMENTS.

YAMABIKO CORP. MMM/YYYY



line emission control system is EVAP (evaporative emissions). Evaporative emissions for California models are only applicable to fuel tanks and fuel feed lines.

An Emission Control Label is located on the engine. (This is an EXAMPLE ONLY, information on label varies by engine FAMILY).

#### EMISSION CONTROL INFORMATION

ENGINE FAMILY: CEHXS.0214KL DISPLACEMENT: 21.2cc EMISSION COMPLIANCE PERIOD: 300HOURS THIS ENGINE MEETS 2012 U.S. EPA EXPLEYP & CALIFORNIA EXH EVP EMISSION REGULATIONS FOR S.O.R.E. REFER TO OWNER'S MANUAL FOR MAINTENANCE SPECIFICATIONS AND ADJUSTMENTS.

YAMABIKO CORP. MMM/YYYY




#### Product Emission Durability (Emission Compliance Period)

The 50 or 300 hour emission compliance period is the time span selected by the manufacturer certifying the engine emissions output meets applicable emissions regulations, provided that approved maintenance procedures are followed as listed in the Maintenance Section of this manual.

### DESCRIPTION

Locate the safety decal(s) on your unit. Make sure the decal(s) is legible and that you understand and follow the instructions on it. If a decal cannot be read, a new one can be ordered from your Shindaiwa dealer. The safety decal is for example only. Your label may appear slightly different.











CONTENTS EB633RT

- 1. Air Cleaner
- 2. Spark Plug
- 3. Recoil Starter Handle
- 4. Spark Arrester Muffler or Spark Arrester Muffler with Catalyst
- 5 Fuel Tank
- 6. Fuel Tank Cap
- 7. Shoulder Harness
- 8 **Blower Pipes**
- 9. Throttle Trigger
- 10 Throttle Position Lever
- 11 Stop Switch
- 12. Throttle Handle
- 13 Choke
- 14 Purge Bulb

# CONTENTS

After opening the carton, check for damage. Immediately notify your retailer or Shindaiwa dealer of damaged or missing parts. Use the contents list to check for missing parts.

- 1 Power Head
- 1 Flex Pipe
- 1 Pipe with Swivel
- 1 Straight Pipe
- 1 Straight Pipe
- 1 Operator's Manual
- 2 Clamps with Screws

**ASSEMBLY** EB633RT

#### **ASSEMBLY**

# **WARNING**


Never perform maintenance or assembly procedures with engine running or serious personal injury may result.

# **Install Blower Pipes**

Assemble clamps (A) and (G) onto both ends of flexible pipe (B).


Note: Clamp with cable guide loop (G) fits elbow end of flexible pipe.


Note: A light lubricant may be used to ease assembly of flexible pipe to blower elbow.



Note: Hang handle freely from blower to assure throttle cable is not twisted before installing handle (E).

- 3. Position throttle cable along the outside of elbow. Loosen knob (H) on handle (E). Align notches in handle with tabs (F) and install onto swivel pipe (C) past long ridges in pipe.
- Assemble swivel pipe into flexible pipe and tighten clamp (A).






- 5. Clip throttle cable into throttle cable guide loop.
- 6. Move handle (E) to desired position. Tighten knob (H) hand tight.

OPERATION EB633RT

7. Assemble straight pipe (K) onto swivel pipe, until you feel light resistance. Do not force connection. Hold swivel pipe and turn straight pipe clockwise, engaging positive locking channels, until connection is firm. Do not force connection.





Note: Blower use will eventually loosen pipe connections. Exclusive positive locking system allows pipes to be tightened. If loosening occurs, remove two straight pipes and install according to instructions 7 & 8.

#### OPERATION

18

# **WARNING**

Moving parts can amputate fingers or cause severe injuries. Keep hands, clothing and loose objects away from all openings. Always stop engine, disconnect spark plug, and make sure all moving parts have come to a complete stop before removing obstructions, clearing debris, or servicing unit. Blower housing might contain shredder blades and other sharp edges that can cause serious injuries if touched, even if engine is off and blades are not moving. Wear gloves to protect hands from sharp edges and hot surfaces.

# WARNING

Operation of this equipment might create sparks that can start fires around dry vegetation. This unit is equipped with a spark arrestor to prevent discharge of hot particles from the engine. Contact local fire authorities for laws or regulations regarding fire prevention requirements.

**OPERATION** EB633RT

# **WARNING**

Engine exhaust IS HOT, and contains Carbon Monoxide (CO), a poison gas. Breathing CO can cause unconsciousness, serious injury, or death. Exhaust can cause serious burns. ALWAYS position unit so that exhaust is directed away from your face and body.

# WARNING

- ◆ This blower should be used for clearing leaves, grass, debris, and dust in yards, gardens, driveways, and parking lots only.
- Always maintain a direct, clear line of site to the unit and the work being performed.
- Always be alert for changes in operation of unit.
- Always shut engine off before transporting unit to new location.
- Always secure the unit during transportation to prevent turnover, fuel spillage, and damage to the unit.

#### Fuel

# **WARNING**

Diesel fuels and alternative fuels, such as E15 (15% ethanol), E85 (85% ethanol) or any fuels not meeting Shindaiwa requirements are NOT approved for use in Shindaiwa 2-stroke or Hybrid 4-stroke gasoline engines. Use of diesel or alternative fuels may cause performance problems, loss of power, overheating, fuel vapor lock, and unintended machine operation, including, but not limited to, improper clutch engagement. Diesel or alternative fuels may also cause premature deterioration of fuel lines, gaskets, carburetors and other engine components.

OPERATION EB633RT

#### **Fuel Requirements**

**Gasoline** - Use fresh (purchased within the last 30 days from the pump) 89 Octane [R+M/2] (mid grade or higher) gasoline known to be good quality. Gasoline may contain up to 10% Ethanol (grain alcohol) or 15% MTBE (methyl tertiary-butyl ether). Gasoline containing methanol (wood alcohol) is **NOT** approved. Use of ECHO branded fuel is recommended to extend engine life in all air-cooled 2-stroke and 2/4-stroke hybrid engines.

**Two Stroke Oil** - A 2-stroke engine oil, such as Shindaiwa branded 2-stroke oils, meeting ISO-L-EGD (ISO/CD 13738) and J.A.S.O. FD Standards must be used. Shindaiwa branded 2-stroke oils meet these standards. Engine problems due to inadequate lubrication caused by failure to use an ISO-L-EGD (ISO/CD 13738) and J.A.S.O. M345-FD certified oil will void the 2-stroke engine warranty.

# **WARNING**

2-Stroke engine oil contains petroleum distillates and other additives that may be harmful if swallowed. Heated oil can release vapors that can cause flash fire, or ignite with explosive force. Read and follow the oil manufacturer's instructions, and observe all safety warnings and precautions for handling flammable liquids. For more detailed safety and first aid information, visit www.echo-usa.com for a copy of the Material Safety Data Sheet.

- **◆ KEEP OUT OF REACH OF CHILDREN.**
- If swallowed, do not induce vomiting. CALL PHYSICIAN OR A POISON CONTROL CENTER IMMEDIATELY.
- WEAR SAFETY GLASSES when mixing or handling.
- AVOID repeated or prolonged skin contact.
- AVOID inhaling oil mists or vapors.

# NOTICE

Shindaiwa branded 2-stroke oils may be mixed at 50:1 ratio for application in all Shindaiwa engines sold in the past, regardless of ratio specified in those manuals.

#### **Handling Fuel**

# **A** DANGER

Fuel is VERY flammable. Use extreme care when mixing, storing or handling, or serious personal injury may result.

- Use an approved fuel container.
- ◆ DO NOT smoke near fuel.
- DO NOT allow flames or sparks near fuel.
- Fuel tanks/cans may be under pressure. Always loosen fuel caps slowly allowing pressure to equalize.
- ◆ NEVER refuel a unit when the engine is HOT or RUNNING!
- DO NOT fill fuel tanks indoors. ALWAYS fill fuel tanks outdoors over bare ground.
- ◆ DO NOT overfill fuel tank. Wipe up spills immediately.
- Securely tighten fuel tank cap and close fuel container after refueling.
- Inspect for fuel leakage. If fuel leakage is found, do not start or operate unit until leakage is repaired.
- ◆ Move at least 3 m (10 ft.) from refueling location before starting the engine.

# **A** DANGER

Gasoline vapor is heavier than air, and can travel along the ground to nearby sources of ignition such as electrical motors, pilot lights, and hot or running engines. Vapors ignited by an ignition source can flash back to the fuel container, resulting in an explosion, fire, serious or fatal injuries, and extensive property damage.

#### Mixing Instructions

- Fill an approved fuel container with half of the required amount of gasoline.
- Add the proper amount of engine oil to gasoline.
- Close container and shake to mix oil with gasoline.
- Add remaining gasoline, close fuel container, and remix.

Fuel to Oil Mix – 50:1 Ratio			
US		Ме	tric
Gas	Gas Oil		Oil
gal.	fl. oz.	L	СС
1	2.6	5	100
2	5.2	10	200
5	13	25	500

OPERATION EB633RT

# NOTICE

Spilled fuel is a leading cause of hydrocarbon emissions. Some states may require the use of automatic fuel shut-off containers to reduce fuel spillage.

#### After use

 Empty the fuel tank prior to storing the unit. Return unused fuel to an approved fuel storage container.

**Storage** - Fuel storage laws vary by locality. Contact your local government for the laws affecting your area. As a precaution, store fuel in an approved, airtight container. Store in a well-ventilated, unoccupied building, away from sparks and flames.

# NOTICE

Stored fuel ages. Do not mix more fuel than you expect to use in thirty (30) days, ninety (90) days when a fuel stabilizer is added.

# NOTICE

Stored 2-stroke fuel may separate. ALWAYS shake fuel container thoroughly before each use.


# NOTICE

Used oil and gasoline, and soiled towels are hazardous waste materials. Disposal laws vary by locality.

# **Starting Cold Engine**

- Recoil starter: Use short pulls only 1/2-2/3 of rope length for starting. Do not allow the rope to snap back in. Always hold the unit firmly.
- Throttle Position / Stop Switch
  Button

Move throttle position lever (A) forward to IDLE position. Slide stop switch (B) forward to RUN position.




#### 2. Choke

Move choke (C) up to COLD START (|--|) position.

#### 3. Purge Bulb

Pump purge bulb (D) until fuel is visible and flows freely in the clear fuel tank return line. Pump bulb an additional 4 or 5 times.



#### 4. Recoil Starter

Pull recoil starter handle (E) until engine fires (5 or 6 pulls maximum).

#### 5. Choke

Move choke (C) down to RUN ( | ↓ | ) position, and if necessary, restart engine.

Note: If engine does not start after 5 pulls, move choke to COLD

START ( position, and repeat steps 4 & 5.


Note: Allow engine to warm up before use.

# **Starting Warm Engine**

The starting procedure is the same as Cold Start except DO NOT close the choke.

#### 1. Throttle Position / Stop Switch Button


Move throttle position lever (A) forward to IDLE position. Slide stop switch (B) forward to RUN position.



#### 2 Recoil Starter

Pull recoil starter handle (E) and engine should start. Do not use choke (C).

Note: If engine does not start after 5 pulls, use cold start procedures.




OPERATION EB633RT

# **Stopping Engine**

Throttle Position / Throttle
 Position Lever

Release throttle trigger (C). Move Throttle Position Lever (A) forward to IDLE position and allow engine to return to idle before shutting off engine.

Stop Switch Button
Slide stop switch (B) to STOP position.



# **WARNING**

If engine does not stop when stop switch is moved to STOP position, close choke - COLD START position - to stall engine. Have your Shindaiwa dealer repair stop switch before using unit again.

# **Operating Blower**

# **WARNING**

Engine exhaust IS HOT, and contains Carbon Monoxide (CO), a poison gas. Breathing CO can cause unconsciousness, serious injury, or death. Exhaust can cause serious burns. ALWAYS position unit so that exhaust is directed away from your face and body.

# **WARNING**

Always wear safety glasses, hearing protection and a face filter mask or serious personal injury may result. Do not point the blower pipe in the direction of people or pets.


# **NOTICE**

Use reduced speed only when performing light-duty tasks or to comply with local noise regulations. Continuous low speed operation may allow fuel/oil residue to build-up on the piston and cause rapid build-up of carbon on the spark arrester screen, resulting in overheating and engine damage. To reduce harmful build-up, run engine at wide open throttle for at least five minutes every hour, and inspect/clean the spark arrester screen after approximately 40 hours of operation.

Read the Safety Section carefully.

To avoid engine damage due to over-revving, do not block blower pipe.

- 1. Use only during appropriate hours.
- 2. Allow the engine to warm up at a fast idle for a few minutes.
- 3. Control engine speed with throttle trigger (C), or throttle position lever (A). Rotate throttle position lever forward for lower speed, back for higher speed.
- Use lower speed to blow dry 4. leaves from walks, patios and drives.
- Additional speed may be 5. necessary to clean grass and leaves from a lawn or flower bed.



- 6. Higher speed may be necessary to move gravel, dirt, snow, bottles or cans from a driveway, street, parking lot or stadium.
- 7. Always stop unit using stop engine procedure.

Note: Never use a higher speed setting than necessary to perform a task. Remember, the higher the engine speed, the louder the blower noise. Minimize dust by using blower at lower speeds. Keep debris on your property. Be Smart - be a good neighbor.

# **MAINTENANCE**

# **WARNING**

Moving parts can amputate fingers or cause severe injuries. Keep hands, clothing and loose objects away from all openings. Always stop engine, disconnect spark plug, and make sure all moving parts have come to a complete stop before removing obstructions, clearing debris, or servicing unit. Allow unit to cool before performing service. Wear gloves to protect hands from sharp edges and hot surfaces.

# **▲** WARNING

Operating a poorly maintained unit can result in serious injuries to operator or bystanders. Always follow all maintenance instructions as written, otherwise serious personal injury can result.

Your unit is designed to provide many hours of trouble free service. Regular scheduled maintenance will help your unit achieve that goal. If you are unsure or are not equipped with the necessary tools, we recommend that you take your unit to a Servicing Dealer for maintenance. To help you decide whether you want to DO-IT-YOURSELF or have the Dealer do it, each maintenance task has been graded. If the task is not listed, see your Dealer for repairs.

# NOTICE

The use of emission control components other than those specifically designed for this unit is a violation of federal law.

#### Skill Levels

**Level 1** = Easy to do. Common tools may be required.

**Level 2** = Moderate difficulty. Some specialized tools may be required.

Level 3 = See your dealer.

Click HERE or go to http://www.echo-usa.com/products/maintenance-kit

or

HERE https://www.shindaiwa-usa.com/you-can.aspx

# **Maintenance Intervals**

COMPONENT/SYSTEM	MAINTENANCE PROCEDURE	REQUIRED SKILL LEVEL
Daily or Before Use		
Air Filter	Inspect/Clean*	1
Choke Shutter	Inspect/Clean*	1
Fuel System	Inspect <sup>1</sup>	1
Cooling System	Inspect/Clean	2
Recoil Starter Rope	Inspect/Clean*	1
Screws/Nuts/Bolts	Inspect/Tighten/Replace*	1
Every Refuel		
Fuel System	Inspect <sup>1</sup>	1
3 Months	•	
Air Filter	Replace*	1
Fuel Filter	Inspect*	1
Fuel Cap Gasket	Inspect*	1
Spark Plug	Inspect/Clean/Replace*	1
Muffler Spark Arrester	Inspect/Clean/Replace*	2
Cylinder Exhaust Port	Inspect/Clean/De-carbon	2
Yearly	•	•
Fuel Filter	Inspect/Replace*	1
Fuel Cap Gasket	Replace*	1

IMPORTANT NOTE - Time intervals shown are maximum. Actual use and your experience will determine the frequency of required maintenance.

#### **MAINTENANCE PROCEDURE NOTES:**

<sup>&</sup>lt;sup>1</sup> Low evaporative fuel tanks DO NOT require regular maintenance to maintain emission integrity.


<sup>\*</sup> Replacement is recommended based on the finding of damage or wear during inspection.

#### Air Filter

#### Level 1.

Parts required: Tune-Up Kit.

- Close choke (COLD START [ ] position). This prevents dirt from entering the carburetor throat when the air filter is removed. Brush accumulated dirt from air cleaner area.
- Remove air filter cover (A). Brush dirt from inside cover.
- 3. Remove air filter (B) and lightly brush debris from filter. Replace filter if it is damaged, fuel soaked, very dirty, or the rubber sealing edges are deformed.
- 4. If filter can be reused, be certain it:
  - Fits tightly in the air filter cavity
  - · Is installed with the original side out
- 5. Install air filter and air filter cover.



#### **Fuel Filter**

#### Level 1.

Parts required: Tune-Up Kit.

# DANGER

Fuel is VERY flammable. Use extreme care when mixing, storing or handling, or serious personal injury may result.

1. Use a clean rag to remove loose dirt from around fuel cap and empty fuel tank.

Do not damage fuel line while removing fuel filter from tank or line.

- 2. Pull the fuel filter from the tank.
- 3. Do not remove the wire coil clamp to remove the fuel filter. Pinch the fuel filter with the fingers on one hand and the fuel line with the other hand. Pull and twist slightly to separate.
- 4. Install the new filter with the reverse action

Note: Federal EPA regulations require all model year



2012 and later gasoline powered engines produced for sale in the United States to be equipped with a special low permeation fuel supply hose between the carburetor and fuel tank. When servicing model year 2012 and later equipment, only fuel supply hoses certified by EPA can be used to replace the original equipment supply hose. Fines up to \$37,500 may be enforced for using an un-certified replacement part.

# Spark Pluq


Level 2.

Parts required: Tune-Up Kit.

# NOTICE

Use only NGK BPM8Y spark plug (BPMR8Y in Canada) otherwise severe engine damage may occur.

- Remove spark plug and check for fouling, worn and rounded center electrode.
- 2. Clean the plug or replace with a new one. DO NOT sand blast to clean. Remaining sand will damage engine.
- Adjust spark plug gap by 3. bending outer electrode.
- Tighten spark plug to 150-170 kgf•cm (130-150 lbf•in). 4.



**shindaiwa**®

X7531126006

# Cooling System

Level 2.

# NOTICE

To maintain proper engine operating temperatures, cooling air must pass freely through the cylinder fin area. This flow of air carries combustion heat away from the engine.

Overheating and engine seizure can occur when:

- · Air intakes are blocked. preventing cooling air from reaching the cylinder.
- Dust and grass build up on the outside of the cylinder. This build up insulates the engine and prevents the heat from leaving.




Removal of cooling passage blockages or cleaning of cooling fins is considered "Normal Maintenance." Any failure attributed to lack of maintenance is not warranted.

#### Cleaning Grill

Brush accumulated debris from intake grill between backpack frame and blower housing.

#### Cleaning Cylinder Fins

- 1. Disconnect spark plug lead from spark plug, and remove engine cover.
- Clean cylinder fins (A) to allow 2. cooling air to pass freely.
- 3. Install engine cover and attach spark plug lead.



# Exhaust System

#### Spark Arrester Screen

Level 2.

Parts required: Spark Arrester Screen, Gasket.

# VOTICE

Carbon deposits in muffler will cause a drop in engine output and overheating. Spark arrester screen must be checked periodically.

- Remove spark plug lead from spark plug, and remove engine cover.
- 2. Remove spark arrester covers (A), gaskets (B), and spark arrester screen (C) from muffler. Replace screen if plugged with carbon deposits.

Note: When cleaning carbon deposits, be careful not to damage the catalytic element inside muffler.




- 3. Install spark arrester screen and cover.
- 4. Install engine cover and attach spark plug lead.

# **Exhaust Port Cleaning**

Level 2.

Parts required: Heat Shield (as required).

- Remove spark plug lead from spark plug, and remove engine cover. 1.
- 2. Place piston at top dead center. Remove muffler (A) and heat shield (B).



3. Use a wood or plastic scraping tool to clean deposits from cylinder exhaust port.



# NOTICE

Never use a metal tool to scrape carbon from the exhaust port. Do not scratch the cylinder or piston when cleaning the exhaust port. Do not allow carbon particles to enter the cylinder.

- 4. Inspect heat shield, and replace if damaged.
- 5. Install heat shield and muffler.
- 6. Tighten muffler mounting bolts (or nuts) to 110-150 kgf•cm (95-130 lbf•in).
- 7. Install engine cover and attach spark plug lead.
- 8. Start engine, and warm to operating temperature.
- 9. Stop engine, and re-tighten mounting bolts (or nuts) to specifications.
- Install muffler cover.

# **Carburetor Adjustment**

# **Engine Break-In**

New engines must be operated a minimum duration of two tanks of fuel break-in before carburetor adjustments can be made. During the break-in period your engine performance will increase and exhaust emissions will stabilize. Idle speed can be adjusted as required.

#### **High Altitude Operation**

This engine has been factory adjusted to maintain satisfactory starting, emission, and durability performance up to 335 m (1,100 ft.) above sea level (ASL) (96.0 kPa). To maintain proper engine operation and emission compliance above 335 m (1,100 ft.) ASL the carburetor may need to be adjusted by an authorized service dealer.

# NOTICE


If the engine is adjusted for operation above 335 m (1,100 ft.) ASL, the carburetor must be re-adjusted when operating the engine below 335 m (1.100 ft.) ASL, otherwise severe engine damage may result.

#### Level 2.

Note: Every unit is run at the factory and the carburetor is set in compliance with emission regulations. Carburetor adjustments, other than idle speed, must be performed by an authorized Shindaiwa dealer.

Before adjustment make sure that:

- Air filter is clean and properly installed.
- Spark arrester screen and muffler are free of carbon.
- · Blower pipes are installed.
- 1. Start engine, run at idle for one minute.
- 2. Complete warm up by running at full throttle for 5 minutes, operating choke twice to clear air from carburetor chambers.
- 3. Check idle speed and reset if necessary. If a tachometer is available, idle speed screw (A) should be set to the specifications found on "Specifications" page of this manual. Turn idle screw (A) clockwise to increase idle speed: counter clockwise to decrease idle speed.



34

# **TROUBLESHOOTING**

# **▲** DANGER

Fuel vapors are extremely flammable and may cause fire and/or explosion. Never test for ignition spark by grounding spark plug near cylinder plug hole, otherwise serious personal injury may result.

ENGINE PROBLEM TROUBLESHOOTING CHART				
Problem	Check	Status	Cause	Remedy
	Fuel at carburetor	No fuel at carburetor	Fuel strainer or fuel line obstructed	Clean or replace See your dealer
Engine starts		No fuel at cylinder	Carburetor	See your dealer
hard or Engine does not start	Fuel at cylinder	Muffler wet with fuel	Fuel mixture too rich	OPEN choke Clean or replace air filter Adjust carburetor See your dealer
Engine starts hard or	Spark at end of plug wire	No spark	Ignition at STOP position Electrical problem Interlock switch	Move ignition away from STOP position. See your dealer
Engine does not start	Spark at plug	Spain	Incorrect gap - Covered with carbon - Fouled with fuel - Plug defective	Adjust to 0.65 mm (0.026 in.) Clean or replace plug

EB633RT STORAGE

ENGINE PROBLEM TROUBLESHOOTING CHART				
Problem	Check	Status	Cause	Remedy
	Air filter	Air filter dirty	Normal wear	Clean or replace
Engine	Fuel filter	Fuel filter dirty	Contaminants or residue in fuel	Replace filter or replace fuel
runs, but dies	Fuel vent	Fuel vent plugged	Contaminated fuel	Clean or replace
or	Spark plug	Plug dirty or worn	Normal wear	Clean and adjust or replace
Engine does not	Carburetor	Improper adjustment	Vibration	Adjust
acceler- ate properly	Cooling system	Cooling system dirty or plugged	Extended operation in dirty or dusty locations	Clean
	Spark arrester screen	Spark arres- ter screen plugged	Normal wear	Replace
Engine does not crank	1	N/A	Internal engine problem	See your dealer

# **STORAGE**

# **WARNING**

During operation the muffler or catalytic muffler and surrounding cover become hot. Always keep exhaust area clear of flammable debris during transportation or when storing, otherwise serious property damage or personal injury may result.

Long Term Storage (Over 30 Days)

# **A** DANGER

Do not store in enclosure where fuel fumes may accumulate or reach an open flame or spark.

Do not store your unit for a prolonged period of time (30 days or longer) without performing protective storage maintenance which includes the following:

- 1. Store unit in a dry, dust free place, out of the reach of children.
- 2. Place the stop switch or lever in the "OFF" position.
- Remove accumulation of grease, oil, dirt and debris from exterior of unit.
- 4. Perform all periodic lubrication and services that are required.
- 5. Tighten all the screws and nuts.
- 6. Drain fuel tank completely. Press purge bulb 6 -7 times to remove remaining fuel from carburetor then drain the tank again. Close choke, start and run the engine until it stops due to lack of fuel.
- 7. Allow engine to cool. Remove the spark plug lead from the spark plug. Remove the spark plug. Pour 7 cc (0.25 oz.) of fresh, clean, two-stroke engine oil into the cylinder through the spark plug hole.
- 8. Pull the recoil starter handle 2-3 times to distribute the oil inside the engine.
- Observe the piston location through the spark plug hole. Pull the recoil handle slowly until the piston reaches the top of its travel and leave it there.
- 10. Install the spark plug. Connect the spark plug lead to the spark plug.
- 11. Remove blower pipe assembly from unit.

#### **SPECIFICATIONS**

MODEL	EB633RT
Length	375 mm (14.8 in.)
Width	485 mm (19.0 in.)
Height	527 mm (20.8 in.)
Weight (dry)	11.0 kg (24.9 lb.)
Engine Type	Air cooled, two-stroke, single cylinder gasoline engine
Bore	48.0 mm (1.89 in.)
Stroke	35.0 mm (1.38 in.)
Displacement	63.3 cc (3.86 in. <sup>3</sup> )
Exhaust	Spark arrester muffler or spark arrester muffler with catalyst
Carburetor	Diaphragm with purge pump
Ignition System	Flywheel magneto, capacitor discharge ignition type
Spark Plug	NGK BPM8Y (BPMR8Y in Canada) Gap 0.65 mm (0.026 in.)
Fuel	Mixed (gasoline and two-stroke oil)
Fuel/Oil Ratio	50:1

#### **EB633RT**

MODEL	EB633RT
Gasoline	Use 89 Octane unleaded. Do not use fuel containing methyl alcohol, more than 10% ethyl alcohol or 15% MTBE. Do not use alternative fuels such as E-15 or E-85.
Oil	ISO-L-EGD (ISO/CD 13738) and J.A.S.O. M345- <u>FD</u> , two-stroke, air-cooled engine oil.
Fuel Tank Capacity	2.0 L. (67.7 US fl. oz.)
Starter System	Automatic recoil starter (centrifugal type)
Idle Speed	2,800 RPM
Wide Open Throttle Speed	7,000 RPM
Average Air Speed w/pipes	87.17 m/sec (195 mph)
Maximum Air Speed w/pipes	104.20 m/sec (233 mph)
Air Volume	18.50 m <sup>3</sup> /min. (651 ft. <sup>3</sup> /min.)
Sound Level at 50 ft. dB(A) scale per ANSI B175.2	74 dB(A)

### PRODUCT REGISTRATION

#### Thank you for choosing Shindaiwa Power Equipment

Please go to http://www.shindaiwa-usa.com to register your new product on-line. It's FAST and EASY! NOTE: your information will never be sold or misused by ECHO Incorporated. Registering your purchase enables us to contact you in the unlikely event of a service update or product recall, and verifies your ownership for warranty consideration.

If you do not have access to the Internet, you can complete the form below and mail to:

ECHO Incorporated, Product Registration, PO Box 1139, Lake Zurich. IL 60047.

02-2(

# STITITATIVE PRODUCT REGISTRATION CARD : TARJETA DE REGISTRO : CARTE D'ENREGISTREMENT DU PRODUIT

Shindaiwa et les offres spéciales par courrier électronique ? 🗖 Oui 🗖 Non Jso primario de la herramienta:□Profesional □ Dueño de casa □ Alquiler Confidential: Information provided will not be shared or sold OPTION EN LIGNE : Enregistrer en ligne et épargner un Do you wish to receive periodic Shindaiwa product information and special ☐ Rental Equip. imbre! Vous serez informe sur les nouveaux produits Shindan et les mises à jour de produit ainsi que les offres spéciales. Simplement visitez le: www.shindaiwa-usa.com Souhaitez-vous recevoir périodiquement de l'information sur les produits X7571120102 ¿Desea usted recibir información periódica y ofertas especiales por correo Visitó usted la pagina web Shindaiwa antes de comprar su producto? Avez-vous visité le site d'Shindaiwa avant de procurer votre produit? Did you visit the Shindaiwa website before purchasing your product? ☐ Location Marchand
Qualité
Garantie Distribuidor ■ Warranty Garantía ☐ Homeowner Calidad □ Quality □ Dealer Jsage principal : Professionnel Residential Quel facteur (facteurs) vous a influencé le plus? electronico sobre el producto Shindaiwa? 🗖 Yes What factor(s) most influenced your purchase? en su compra? www.shindaiwa-usa.com Experiencia Anterior ■ Prior Experience □ Professional Expérience 2 D Margue influenció más □ Brand Marca ☐ Precio ☐ Price Pri offers by e-mail? Thes Primary use of tool: ☐ Friend/Family producto y/o se le enviara información sobre los nuevos pro-ductos Shindaiwa y las ofertas especiales. Simplemente visite: ¿Qué factor(es) i No D ☐ Performance Performance UPCION PUK INTEKNET: ¡Registrese en la pagina web y ahorre una estampilla! Le alertaran sobre actualizaciones del ■ Amigo/Familia Ami/Famille ž ■ Confiabilidad Registrese en la pagina web □ Reliability 18779867783 Fiabilité Yes ino 🗖 S O www.shindaiwa-usa.com Regisfering your purchase enables us to contact you in the unikely event of a service update or product resall and verifies your ownership in the event of loss. It fregisters to contact of the service of the productor yethrication the propled at encaso de note to definite. On the service of série Code Postal g Date of Purchase: Fecha de la Compra Š **OPCIÓN POR INTERNET:** Serie Zip Code : Código Postal : Numero de Please Print : Por Favor Enscriba Con Letra De Molde : En Lettre Carré S.V.P. Where Purchased : Nombre del Almacén donde fue Comprado : Lieu d'achat E-Mail Address : Dirección De Correo Electrónico : Courrier Électronique Date de l'achat Serial Number Purchaser's Name : Nombre del Comprador : Nom de l'acheteu ONLINE OPTION: Register online and save a stamp! You will be alerted of product updates and/or be sent new Shindalwa State: Estado: Province product information and special offers. Simply go to: Phone Number : Número De Teléfono : Téléphone de modéle www.shindaiwa-usa.com Model Number: Numero del Modelo: No. Address : Dirección : Adresse City: Ciudad: Ville

X7531126006 39

P45314003637 - P45314999999 P53214001001 - P53214999999



# **ECHO INCORPORATED**

400 Oakwood Road Lake Zurich, IL 60047 www.shindaiwa-usa.com